

808 nm 3 W Laser Diode

- High Power CW Operation- 3 watts
- High Brightness- 150 μm emitter size
- Wavelength 808 nm standard
- Divergence $10^\circ \times 32^\circ$ FWHM

The LDX-3315-808 laser diode is a high power, high brightness, multimode infrared laser diode. These broad-area, gain-guided lasers offer high efficiency, low threshold current, and excellent reliability.

These devices are available on an open heatsink (C-mount) package, in hermetically sealed TO-3 packages, as well as other package options; please inquire.

Device ratings:

Parameter	Min.	Typ.	Max.	Units
Output Power @ 20 °C		3000	3500	mW
Threshold Current	200	350	600	mA
Operating Current at Rated Power	2600	2800	3700	mA
Operating Temperature	0	20	40	°C

Device characteristics at 20°C and at 3000 mW output power:

Parameter	Min.	Typ.	Max.	Units
Forward Voltage	1.8	2.0	2.2	Volts
Wavelength	802	806	808	nm
Spectral Width		2	4	nm (FWHM)
Divergence- Parallel		10	12	degrees (FWHM)
Divergence- perpendicular	28	32	36	degrees (FWHM)
Polarization Ratio		>50:1		
Aperture Size		150 x 1		μm
Slope Efficiency	1.0	1.2	1.3	mW/mA